

Panel Plus

Material

Composed of steel single or double vertical collectors at rear with steel horizontal radiation tubes. The radiation tubes are welded at the inside of the collector by gas and with steel as sole addition.

Therefore no welding seams are visible at the outside of the radiator.

Pressure test: 6 bar

Working pressure: 4.6 bar

Composition

Panel Plus Vertical

The oval radiation tubes (60 x 10.4 x 1.5 mm) are vertical and parallel lengthways placed on the horizontal collector (37 x 35 x 2 mm) with an interdistance of 3 mm. The radiation tubes are provided with convection fins. All fixings points are welded to the radiator. The supports to fit to the wall are supplied with the standard delivery. Transparency : none.

Panel Plus Horizontal

The oval radiation tubes (60 x 10.4 x 1.5 mm) are horizontal and parallel lengthways placed on the vertical collector with an interdistance of 3 mm. The radiation tubes are /are not provided with convection fins. The types which start from 24.9 cm high may have convection fins only from 6.8 cm of the top and they cover maximum 9 radiation tubes. For the types until 18.6 cm max height, the convection fins are placed up to 0.5 cm of the top end of the radiator and cover all radiation tubes. All models are supplied with a pre-mounted grille.

Single collector: 37 x 35 x 2 mm

Double collector: 65 x 38 x 2 mm

All fixing points are welded to the radiator. The supports to fit to the wall are supplied with the standard delivery. Transparency: none.

Finish

The radiators are sandblasted, degreased, phosphated, electrostatically lacquered with epoxy-polyester powder and finally stove enamelled at 200 °C. This high quality finish offers an optimal scratch resistance and is very easy to maintain. Thickness of the lacquer: min 80 µ.

Colour

The radiator is lacquered in the colour sandblast grey metallic 001 / white (RAL 9010) / white (RAL 9016) / other (see colour chart)

Connections

The sockets 1/2" at the bottom or at the side end of the collector are integrated in the collectors and hence invisible. The connections may be ordered at customer choice at the bottom, the top end or at the side end of radiator. Provided with a chrome-plated air vent 1/2" and drain cock 1/2". Output in Watts, measured in accordance with EN 442.

How to install

The building services engineer chooses the radiators considering following conditions:

- A heat output calculation according to the standard.

The heat output and the dimensions of the Panel Plus radiators according to EN 442.

- The radiators may be wall fitted with the wall fixings supplied / fitted to the floor with supplied feet.

- The specially designed thermostatic connection sets / thermostatic Jaga Deco / Jaga-Pro valves / manual Jaga Deco valves can be connected to plastic central heating service pipes / RPE/ALU. tube / copper tube/ steel pipe.

- Jaga thermostatic heads / Jaga Deco thermostatic heads chrome / Jaga Deco thermostatic heads chrome/ white / Jaga Comap thermostatic heads silver / not to be / to be fitted.

Options

- Jaga Deco valves.

- Radiation prevention screen for free-standing skirting model.