

TEMPO LST

MATERIAL

- › Low-H₂O heat exchanger is composed of round, seamless circulation tubes made of pure red copper, with pure aluminium fins and two brass collectors for left or right 1/2" same end connection. Air vent 1/8" and drain cock 1/2" are included.
Pressure test: 20 bar
Working pressure: 10 bar
- › Brackets are included and made of galvanised steel plate of 1 mm; supplied to be installed with a maximum intermediate distance of 1.05 m.
- › The front panels: galvanised steel plates of 0.86 mm thick, double profiled in length. Supplied with small positioning holes and slots to assemble front panels to side panel with easy click system.
- › Side panels: profiled galvanised steel plate of 1 mm thick
- › The top grille: galvanised steel plate of 0.80 mm thick, profiled backwards angled steel plate with angled topside. At corners the grille is supplied with high standard synthetic angled corner pieces in same finish as casing.
- › The freestanding model: front and back panels are identical, grille and side panels come adapted to this model. The feet are telescopically adjustable for placement on [finished floor / concrete floor](#).

COLOUR

- › Heat exchanger electrostatically lacquered with anthracite grey epoxy-polyester RAL 7024.
- › The casing is in a scratch resistant structured polyester finish in white (RAL 9010), UV resistant due to ASTM G53.

Integral Low-H₂O technology ensures that the casing remains safe to touch without risk of burns, even at high flow temperatures, in accordance with NHS Estates specification guidance.

Manufacturer: Jaga,
Type: Tempo LST.

Outputs meet standard EN 442.

OPTIONS

- › Locks, 2 per casing. The casing cannot be detached without tools.
- › Pencil-proof grille, avoiding the possibility of smaller objects or waste falling within the casing. Lacquered in the same colour as the casing.
- › Top valve.
- › Tempo LST freestanding: feet in the same colour of the casing.
- › Extended air vent for heat exchanger type 10 / 15 / 20.
- › Brush for easy cleaning of the underside of the heat exchanger.



HOW TO INSTALL

The building services engineer chooses the heating elements considering the following conditions:

- › a heat output calculation according to the standard.
- › Tables of heat outputs and dimensions for [Tempo LST / Cocoon LST / Sentinel LST / Maxi LST](#) elements, according to EN 442
- › the normal fitting position for the heating elements is under the window, and to achieve the most aesthetically pleasing appearance the casing should not be wider than the total width of the window. The height of the casing has to be a function of the heat loss calculations; aesthetically narrower types are preferable. Types 20 and 21 are more suitable for utility areas.
- › when only small outputs are required, the casing can be extended, if necessary, to fill up the total window space
- › the minimum space requirement under the heating elements is:
for [Tempo LST / Cocoon LST / Sentinel LST / Maxi LST](#)
 - 10 cm for types 06, 10 and 11
 - 12 cm for types 15 and 16
 - 15 cm for types 20 and 21
- › as minimum space between the top of the casing and the extended window sills, the above mentioned dimensions have to be applied.
- › the heat exchangers will be connected to a two pipe system, with a same end connection. The heat exchangers are equipped with 1/2" brass collector, 1/8" air vent and a 1/2" drain cock. The flow valve always has to be fitted to the top connection of the heat exchanger. The specially designed thermostatic [Jaga Danfoss / Jaga / Jaga type 6 / Jaga Pro / Jaga Comap / Jaga Top](#) valves can be connected to [plastic central heating service pipes/ RPE/ALU. tube / copper tube/ steel pipe](#). The valve body is concealed within the standard casing
- › [Jaga Danfoss type RA thermostatic heads white / Jaga Danfoss type RAX thermostatic heads white / Jaga Danfoss type RAX thermostatic heads chrome / Jaga thermostatic heads / Jaga Deco thermostatic heads chrome / Jaga Deco thermostatic heads chrome-white / Jaga Comap thermostatic heads silver / remote controlled Jaga thermostatic heads / Jaga Deco thermostatic heads chrome-white with sensor at distance / not / to be fitted.](#)